



Cloud7 2x2

Cloud Managed Wi-Fi 7 2x2 Indoor Access Point

Overview

EnGenius Cloud Managed Wi-Fi 7 2x2 Access Point ECW510 supports dual concurrent 802.11be Wi-Fi 7 architecture, delivering supercharged speeds up to 4,300 Mbps (5 GHz), and up to 700 Mbps (2.4 GHz). With WPA3 & WPA2-AES authentication support, remote monitoring & troubleshooting, and Mesh Wireless Support for optimized signal quality, it's easy to set up and manage an unlimited number of APs with the EnGenius Cloud App.



Features & Benefits

- Dual concurrent 802.11be Wi-Fi 7 architecture & backward-compatible
- Supercharged speeds up to 4,300 Mbps (5 GHz) & up to 700 Mbps (2.4 GHz)
- 2.5 GbE realizes greater throughput and supports 802.3at and PoE injector input for flexible installation over 100 meters (328 feet)
- WPA3 & WPA2-AES authentication support
- Cloud Managed with AP & Mesh mode
- Quick-scan device register & configuration and remote monitoring & troubleshooting
- Cloud manage an unlimited number of APs from anywhere with the EnGenius Cloud App
- Mesh Wireless Support simplifies setup, optimizes signals & self-heals

Technical Specifications

Technical Specifications

Standards

IEEE 802.11ax on 2.4 GHz

IEEE 802.11ax on 5 GHz

IEEE 802.3 u/ab

Backward compatible with 802.11a/b/g/n/ac/ax

Antenna

2 x 2.4 GHz: 3 dBi(Integrated Omni-Directional)

2 x 5 GHz: 5 dBi(Integrated Omni-Directional)

Physical Interfaces

1 x 2.5GE Port (PoE+)

1 x DC Jack

1 x Reset Button

LED indicators

1 x Multi-color LED

Power Source

Power-over-Ethernet: 802.3at Input

12VDC /1.5A Power Adapter

Maximum Power Consumption

18.7W

Wireless & Radio Specifications

Operating Frequency

Dual-Radio Concurrent 2.4 GHz & 5 GHz

Operation Modes

Managed mode: AP, AP Mesh, Mesh

Frequency Radio

2.4 GHz: 2400 MHz ~ 2482 MHz

5 GHz: 5150 MHz ~ 5250 MHz, 5250 MHz ~ 5350 MHz, 5470 MHz ~ 5725 MHz, 5725 MHz ~ 5850 MHz, 5850MHz ~ 5895MHz

Transmit Power

Up to 23 dBm on 2.4 GHz

Up to 21 dBm on 5 GHz

(Maximum power is limited by regulatory domain)

Radio Chains

2 x 2:2

SU-MIMO

Two(2) spatial stream Single User (SU) MIMO for up to 700 Mbps wireless data rate with EHT40 bandwidth to a 2x2 wireless device under the 2.4GHz radio.

Two(2) spatial stream Single User (SU) MIMO for up to 4,300 Mbps wireless data rate with EHT240* to a 2x2 wireless device under the 5GHz radio.

MU-MIMO

Two(2) spatial stream MU-MIMO for up to 700 Mbps wireless data rate with EHT40 bandwidth to a 2x2 wireless device under the 2.4GHz radio.

Two(2) spatial stream MU-MIMO for up to 4,300 Mbps wireless data rate with EHT240* to a 2x2 wireless device under the 5GHz radio simultaneously.

*EHT 240 MHz bandwidth is available on the 5GHz band and may be supported in some regions/countries due to regulatory restrictions.

Supported Data Rates

802.11be:

2.4 GHz: Max 700 (MCS0 to MCS13, NSS = 1 to 4)

5 GHz: Max 4,300 (MCS0 to MCS13, NSS = 1 to 4)

802.11ax:

2.4 GHz: 9 to 574 (MCS0 to MCS11, NSS = 1 to 4)

5 GHz: 18 to 2,400 (MCS0 to MCS11, NSS = 1 to 4)

802.11b: 1, 2, 5.5, 11

802.11a/g: 6, 9, 12, 18, 36, 48, 54

802.11n: 6.5 to 600 (MCS0 to MCS31)

802.11ac: 6.5 to 1,733 (MCS0 to MCS9, NSS = 1 to 4)

Supported Radio Technologies

802.11be/ax: Orthogonal Frequency Division Multiple Access(OFDMA)

802.11a/g/n/ac: Orthogonal Frequency Division Multiple (OFDM)

802.11b: Direct-sequence spread-spectrum (DSSS)

Channelization

802.11be supports extreme high efficiency (EHT) –EHT 20/40/80/160/240/320MHz

802.11ax supports high efficiency throughput (HE) –HE 20/40/80/160 MHz

802.11ac supports very high throughput (VHT) –VHT 20/40/80 MHz

802.11n supports high throughput (HT) –HT 20/40 MHz

802.11n supports high throughput under the 2.4GHz radio –HT40 MHz (256-QAM)

802.11n/ac/ax packet aggregation: A-MPDU, A-SPDU

Supported Modulation

802.11be: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM, 4096-QAM

802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM

802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM

802.11b: BPSK, QPSK, CCK

Max Concurrent User

512

Client Balancing

Yes

Auto Channel Selection

Yes

Technical Specifications

Management Features

Multiple BSSID

8 SSIDs on both 2.4GHz, 5GHz and 6GHz bands

VLAN Tagging

Supports 802.1q SSID-to-VLAN Tagging

Cross-Band VLAN Pass-Through

Management VLAN

Spanning Tree

Supports 802.1d Spanning Tree Protocol

QoS (Quality of Service)

Compliance With IEEE 802.11e Standard

WMM

SNMP

v1, v2c, v3

MIB

I/II, Private MIB

Fast Roaming

802.11r/k

Wireless Security

WPA2-PSK

WPA2-Enterprise

WPA3-PSK

WPA3-Enterprise

Hide SSID in Beacons

Wireless STA (Client) Connected List

Client Isolation

Client Access Control

Interface

IPv4, IPv6

Local Web Access

Supports HTTP or HTTPS

Environmental & Physical

Temperature Range

Operating: 32°F~104°F (0 °C~40 °C)

Storage: -40 °F~176 °F (-40 °C~80 °C)

Humidity (non-condensing)

Operating: 90% or less

Storage: 90% or less

Dimensions & Weight

Weight

660 g

Dimensions

160 x 160 x 32 mm

Package Contents

1 – ECW510 Cloud Managed Indoor Access Point

1 – Ceiling Mount Base (9/16" Trail)

1 – Ceiling Mount Base (15/16" Trail)

1 – Ceiling and Wall Mount Screw Kit

1 – Product Card

Compliance

Regulatory Compliance

FCC

CE

IC


UKCA

VCCI


AU

Antennas Patterns


2.4GHz




2.4GHz




5GHz



5GHz



Hardware Overviews



EnGenius Networks Japan 株式会社 | Tokyo, Japan
Email: jp.support@engeniustech.com
Website: www.engeniustech.com/jp
Local contact: (+81) 3 6809 6608

EnGenius Networks Europe B.V. | Eindhoven, Netherlands
Email: support@engeniustech.com
Website: www.engeniustech.com/eu
Local contact: (+31) 40 8200 887

恩碩科技股份有限公司 | Taiwan, R.O.C.
Email: sales@engeniustech.com.tw
Website: www.engeniustech.com/tw
Local contact: (+886) 933 250 628

EnGenius Technologies | Costa Mesa, California, USA
Email: support@engeniustech.com
Website: www.engeniustech.com
Local contact: (+1) 714 432 8668

EnGenius Networks Singapore Pte Ltd. | Singapore
Email: techsupport-sg@engeniustech.com
Website: www.engeniustech.com/apac
Local contact: (+65) 6227 1088

EnGenius Technologies Canada | Ontario, Canada
Email: support@engeniustech.com
Website: www.engeniustech.com
Local contact: (+1) 905 940 8181

EnGenius Networks Dubai | Dubai, UAE
Email: support-me@engeniustech.com
Website: www.engeniustech.com/apac
Local contact: (+971) 4 339 1227

Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his/her own expense. Prior to installing any surveillance equipment, it is your responsibility to ensure the installation is in compliance with local, state and federal video and audio surveillance and privacy laws.

Version 1.2 08/ 28/ 2025

